

Declaration of Performance

N° DoP: 2023-002 SA47



Unique identification code of the product-type:

ONDUTISS® FACADE OPEN UVFR 210, ONDUTISS® FACADE OPEN UVFR 210 TT

Intended use/es:

Flexible sheets for underlays for walls - In walls of buildings

Manufacturer:

Onduline
24, quai Gallieni
92150 Suresnes - France

System/s of AVCP:

System 3

Harmonised standard :

EN 13859-2:2010

Notified body/ies:

0761 - Materialprüfanstalt für das Bauwesen (MPA BS)
0799 - Kiwa GmbH Niederlassung TBU

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	B s1 d0	-	-	EN 13859-2:2010
Watertightness	W1	-	-	
Water vapour resistance factor Sd (m)	0,13	-0,03	+0,03	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	340 / 240	-30	+30	
Elongation at maximum load (longitudinal/transverse direction) (%)	50 / 70	-15	+15	
Resistance to tearing (longitudinal/transverse direction)	210 / 300	-30	+30	
Cold bending behaviour (°C)	<-20	-	-	
Durability of resistance to water penetration	W1	-	-	
Durability of tensile strength (longitudinal/transverse direction)	320 / 220	-30	+30	
Durability of elongation (longitudinal/transverse direction)	40 / 60	-15	+15	
Dangerous substances	NPD			

NPD* : No Performance Declared

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v02

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Nay TAWILE', is written over a horizontal line.

Nay TAWILE
Suresnes, 22/03/2024